

demista

GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11

Power Rating: 200W/m²

Standard Voltage: 12V AC

Insulation Class: 2-double insulated

Thickness: 1 mm

IP Rating: 44

Cable connector: 30 x 40 x 5mm

Cable: 1m twin core 1.0mm² oval

Adhesive: acrylic

Material: Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 10 -15°C above ambient room temp.

Heating time: 3-5 minutes to start heating the mirror (depending on ambient room temperature)

Heat spread: Approximately 30% area around the pad

<i>demista</i> TM Model Number	Nominal Power (Watts)	Dimen- sions(mm)	Resistance range (Ohms)	Current(Amps)
7505	7	274 x 150	19.6-22.8	0.65
7510	15	274 x 265	9.1-10.6	1.25
7520	25	584 x 274	5.5 – 6.4	2.0
7525	36	462 x 424	3.9-4.6	3.0
7530	50	524 x 520	2.7-3.2	4.0
7533	43	800 x 300	3.1-3.6	3.6
7535	80	785 x 524	1.7-2.0	6.5
7540	100	1040 x 524	1.37-1.6	8.00
7550	150	1505 x 524	.914-1.07	12.5

10 year warranty against any manufacturing fault, providing *demista*TM is fitted strictly in accordance with instructions supplied.

demista[®]

DEMISTA is a registered trademark of Demista Ltd

Telford Road, Glenrothes, Fife, KY7 4NX

Tel: +44 (0) 1932 866600

Email: sales@demista.co.uk

Fax +44 (0) 1932 866688

www.demista.co.uk

demista®

DEMISTA is a registered trademark of Demista Ltd
Telford Road, Glenrothes, Fife, KY7 4NX

Tel: +44 (0) 1932 866600
Email: sales@demista.co.uk

Fax +44 (0) 1932 866688
www.demista.co.uk