

GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11

Power Rating: 200W/m²

Standard Voltage: 12V AC

Insulation Class: 2-double insulated

Thickness: 1 mm

IP Rating: 44

Cable connector: 30 x 40 x 5mm

Cable: 1m twin core 1.0mm² oval

Adhesive: acrylic

Material: Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 10 -15°C above ambient room temp.

Heating time: 3-5 minutes to start heating the mirror (depending on ambient room temperature)

Heat spread: Approximately 30% area around the pad

| Demista™ Model Number | Nominal Power (Watts) | Dimensions(mm) | Resistance range (Ohms) | Current(Amps) |
|--------------------------|--------------------------|----------------|-------------------------------|---------------|
| 7505 | 7 | 274 x 150 | 19.6-22.8 | 0.65 |
| 7510 | 15 | 274 x 265 | 9.1-10.6 | 1.25 |
| 7520 | 25 | 584 x 274 | 5.5 – 6.4 | 2.0 |
| 7525 | 36 | 462 x 424 | 3.9-4.6 | 3.0 |
| 7530 | 50 | 524 x 520 | 2.7-3.2 | 4.0 |
| 7533 | 43 | 800 x 300 | 3.1-3.6 | 3.6 |
| 7535 | 80 | 810 x 524 | 1.7-2.0 | 6.5 |
| 7540 | 100 | 1040 x 524 | 1.37-1.6 | 8.00 |
| 7550 | 150 | 1550 x 524 | .914-1.07 | 12.5 |

10 year warranty against any manufacturing fault, providing **demista™** is fitted strictly in accordance with instructions supplied.

